

| Product parameters | | |
|----------------------------|--|-------|
| model | CH220-A1630H | |
| Connection method | HDMI digital high-definition interface directly connected to the monitor | |
| photographic eyepiece | 0.5X | |
| industrial lens | 0.7X--4.5X continuous zoom | |
| working height | 35mm--250mm | |
| Field of view | Standard 2.6mm--22mm Add 0.6mm-34mm | |
| gain | 25X--200X (refer to 21.5 display), the maximum can be increased to 800X | |
| Focusing mechanism | Manual knob type up and down focusing, focusing stroke 1mm--60mm | |
| Base material size | Anti-static paint aluminum length 320mm*width 260mm*thickness 25mm | |
| Center working distance | 150mm | |
| Lighting system | machine vision special High-brightness LED, brightness dimmable. | |
| Image acquisition system | <ul style="list-style-type: none"> ◆Using 16 million pixel Sony CMOS image sensor; ◆Using 1/2 inch image sensor; ◆HDMI 1080P 60 frame image output; ◆Support image freeze; ◆Support electronic zoom function; ◆Support manual/automatic exposure/one-key exposure, exposure Compensation value adjustment; ◆Support manual/automatic white balance/one-key white balance, red, green and blue adjustable; ◆Provide 8 line drawing functions, line color, thickness, position can be adjusted; ◆Provide center cross line display/close ; ◆Support remote control operation, clearer images without shaking when taking pictures; ◆Support Chinese and English menu languages; ◆Support shutdown setting parameter saving; ◆Using CNC fine milling technology to process aluminum alloy shell; | |
| The standard configuration | Industrial Camera CH-A1630 | 1 |
| | Industrial camera power adapter | 1 |
| | Industrial lens 0.7X-4.5X continuous zoom lens | 1 |
| | Adjustable high-brightness LED light source for machine vision | 1 |
| | Microscope special bracket | 1 set |
| | HDMI digital high-definition cable | 1 |
| Optional accessories | monitor | |

with 22inch screen

